



Type SS Pan Mixers



Product Categories: [Concrete Mixers](#)

Product Page: <https://www.kilworthmachinery.co.uk/product/type-ss-favorite/>

Product Summary

Fliegl Mixers. The Original mobile Pan Mixer. Fliegl mixers have been sold in the UK by Kilworth for 20 years with well over 3000 units sold.

The basic pan mixer is tractor 3 point linkage mounted and PTO driven as standard. For mobile mixing using a telescopic handler or backhoe loader an hydraulic kit is available.

For stationary mixing, for example with a batching plant, electric motor drive units are available. SS type mixers are filled through the mesh grid on the top of the mixer, usually with a loader, backhoe bucket, skid steer etc.

Computer controlled electrically driven mixing plants up to 2.5 cbm also available.

Product Description

Fliegl Mixers. The Original mobile Pan Mixer. Fliegl mixers have been sold in the UK by Kilworth for 25 years with well over 3000 units sold.

The basic pan mixer is tractor 3 point linkage mounted and PTO driven as standard. For mobile mixing using a telescopic handler or backhoe loader an hydraulic kit is available.

For stationary mixing, for example with a batching plant, electric motor drive units are available. SS type mixers are filled through the mesh grid on the top of the mixer, usually with a loader, backhoe bucket, skid steer etc.

Computer controlled electrically driven mixing plants up to 2.5 cbm also available.

The SS mixer is a heavy duty mixer with 2 stage reduction gearbox (except 401SS) and is suitable for contractors, farmers etc.

Mixers can be built to suit a wide variety of applications. Please contact Kilworth for advice if you have a special application.

Specification

- CAT 2 three point linkage
- Manual operated rear discharge chute
- Splash guard.
- PTO shaft with shear bolt protection.
- Fork slots in mixer frame.
- High quality steel pan.

Optional Extras

- Hydraulic Drive Kits
- Electric Motor Drive Kits (SS Models only)
- Hydraulic discharge opening
- Wheel and chassis kits
- Swinging discharge chute

Models

[table cols="Model, Capacity cu.m(kg), Weight full, Tractor min HP " data=""
600 Favorite, 0.5 (1100 Kg), 1550, 50,
800 Favorite, 0.75 (1680 Kg), 2200, 80,
401SS, 0.4 (900 Kg), 1300, 45,
602SS, 0.6 (1350 Kg), 1900, 60,
802SS, 0.8 (1800 Kg), 2400, 80,
1002SS 1.0 (2250 Kg), 3000, 100
"]